

technical specifications for SA subwoofere



specifications / model	SE200	SE175
	activ subwoofer	activ subwoofer
frequency range	22 - 160 Hz (+/- 3 dB)	30 - 160 Hz (+/- 3 dB)
crossover network	40 - 160 Hz (variabel 24 dB/oct.)	40 - 160 Hz (variabel 24 dB/oct.)
built-in amplifier	380 Watt impuls	380 Watt impuls
input voltage	115 or 230 Volt	115 or 230 Volt
woofer	1 pcs. 10" W25	1 pcs. 8" W21
passive woofer	-	-
principle	var.bass reflex/sealed chamber	var.bass reflex/sealed chamber
magnetic shielding	yes	yes
sand chamber	-	-
packing	individually	individually
weight loudspeaker (kgs)	21,85	21,5
dimensions (WxHxD) cm	35 x 35 x 35	35 x 35 x 35
packing dimensions (WxHxD) cm	50 x 45 x 48	50 x 45 x 48
shipping weight (kgs)	25,35	24,85
recommended placement	floor, min. 8 cm from backwall	floor, min. 8 cm from backwall
finish	finish overview	finish overview
other enamel paint available on special order	-	-
2 years factory warranty from purchase date*	yes	yes
included accesories	8 spikes with nuts 8 rubber feet	8 spikes with nuts 8 rubber feet
recommended accesories	SPK1 8 spikes with nuts	SPK1 8 spikes with nuts

specifications are subject to change without further notice.

* System Audio A/S grants 2 years warranty against manufacturing defects. The warranty does not cover misuse. The dealer or an associated workshop performs repair or inspection. The warranty is valid, as long as there have been no modifications to the construction.